

* BÜFA®-UP HARZ 65 T (MINKE I)

Date revised: 30.05.2015

7000165

Version: 7 / GB

Master No. M-401

Print date: 16.06.15

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

BÜFA®-UP HARZ 65 T (MINKE I)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Purpose of use: Raw substance formulas for manufacturing shaped parts from unsaturated polyester / vinyl ester resins.

1.3. Details of the supplier of the safety data sheet

Address

BÜFA Composite Systems
GmbH & Co. KG
Hohe Looge 2-8
26180 Rastede

Telephone no. +49 4402 975-0

Fax no. +49 4402 975-400

Information provided Department product safety / +49 4402 975-415
by / telephone

E-Mail produktsicherheit-compositesystems@buefa.de

1.4. Emergency telephone number

Giftzentrale Goettingen: +49 551 19240

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (Regulation (EC) No. 1272/2008)

Flam. Liq. 3	H226
Acute Tox. 4	H332
Skin Irrit. 2	H315
Eye Irrit. 2	H319
Skin Sens. 1	H317
Repr. 2	H361d
STOT SE 3	H335
STOT RE 1	H372

The product is classified and labelled in accordance with Regulation (EC) No 1272/2008
For explanation of abbreviations see section 16.

2.2. Label elements

Labelling according to regulation (EC) No 1272/2008

Hazard pictograms



Signal word

Danger

Hazard statements

H226	Flammable liquid and vapour.
H332	Harmful if inhaled.
H315	Causes skin irritation.

* BÜFA®-UP HARZ 65 T (MINKE I)

Date revised: 30.05.2015

7000165

Version: 7 / GB

Master No. M-401

Print date: 16.06.15

H319 Causes serious eye irritation.
 H317 May cause an allergic skin reaction.
 H361d Suspected of damaging the unborn child.
 H335 May cause respiratory irritation.
 H372 Causes damage to organs through prolonged or repeated exposure:

Precautionary statements

P210.9 Keep away from sparks, open flames and other ignition sources. No smoking.
 P260.8 Do not breathe vapours/spray.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P308+P313 IF exposed or concerned: Get medical advice/attention.

Hazardous component(s) to be indicated on label (Regulation (EC) No. 1272/2008)

contains Styrene;Xylene;2-(N-ethylanilino)ethanol

2.3. Other hazards

The product does not contain PBT/vPvB-substances.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Hazardous ingredients****Styrene**

CAS No. 100-42-5
 EINECS no. 202-851-5
 Registration no. 01-2119457861-32-XXXX
 Concentration >= 29 < 50 %

Flam. Liq. 3 H226
 Skin Irrit. 2 H315
 Acute Tox. 4 H332
 Eye Irrit. 2 H319
 STOT SE 3 H335
 STOT RE 1 H372 Organs: Ear; Route of exposure: inhalative
 Asp. Tox. 1 H304
 Repr. 2 H361d

2-(N-ethylanilino)ethanol

CAS No. 92-50-2
 EINECS no. 202-160-9
 Concentration >= 1 < 3 %

Acute Tox. 4 H302
 Eye Dam. 1 H318
 Skin Sens. 1 H317

Xylene

CAS No. 1330-20-7
 EINECS no. 215-535-7
 Registration no. 01-2119488216-32-XXXX
 Concentration >= 1 < 10 %

Skin Irrit. 2 H315
 Flam. Liq. 3 H226
 Acute Tox. 4 H332
 Acute Tox. 4 H312

* BÜFA®-UP HARZ 65 T (MINKE I)

Date revised: 30.05.2015

7000165

Version: 7 / GB

Master No. M-401

Print date: 16.06.15

Eye Irrit. 2	H319
STOT SE 3	H335
STOT RE 2	H373
Asp. Tox. 1	H304

Complete text of hazard statements in chapter 16

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Adhere to personal protective measures when giving first aid. Remove soiled or soaked clothing immediately, do not allow to dry.

After inhalation

Remove the casualty into fresh air and keep him calm. Irregular breathing/no breathing: artificial respiration. In the event of symptoms take medical treatment.

After skin contact

Wash off immediately with soap and water.

After eye contact

In case of contact with the eyes, rinse immediately for at least 15 minutes with plenty of water. Seek medical advice immediately. Remove contact lenses

After ingestion

Rinse mouth thoroughly with water. Summon a doctor immediately. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. If individual is drowsy or unconscious place in recovery position (on left side, with head down).

4.2. Most important symptoms and effects, both acute and delayed

The following symptoms may occur: Headache, Dizziness, Nausea

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam, Dry powder, Carbon dioxide

Non suitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

In case of combustion evolution of dangerous gases possible. In the event of fire the following can be released: Carbon monoxide (CO); Nitrogen oxides (NO_x); dense black smoke

5.3. Advice for firefighters

Use self-contained breathing apparatus.

Collect contaminated fire-fighting water separately, must not be discharged into the drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with skin, eyes and clothing. Use personal protective clothing. Keep away sources of ignition. Ensure adequate ventilation. Use breathing apparatus if exposed to vapours/dust/aerosol.

6.2. Environmental precautions

Do not allow to enter drains or waterways. Do not discharge into the subsoil/soil. Prevent spread over a

* BÜFA®-UP HARZ 65 T (MINKE I)

Date revised: 30.05.2015

7000165

Version: 7 / GB

Master No. M-401

Print date: 16.06.15

wide area (e.g. by containment or oil barriers).

6.3. Methods and material for containment and cleaning up

Pick up with absorbent material (eg sand, kieselgur, acid binder, universal binder, sawdust). When picked up, treat material as prescribed under Section 13 "Disposal".

6.4. Reference to other sections

Information regarding Safe handling, see Section 7. Information regarding personal protective measures, see Section 8. Information regarding waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Provide good ventilation of working area (local exhaust ventilation if necessary). Observe the usual precautions for handling chemicals.

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Vapours can form an explosive mixture with air.

7.2. Conditions for safe storage, including any incompatibilities

Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Keep container tightly closed and dry in a cool, well-ventilated place. Protect from heat and direct sunlight.

7.3. Specific end use(s)

No information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limit values

Styrene

List	EH40			
Type	WEL			
Value	430	mg/m ³	100	ppm(V)
Short term exposure limit	1080	mg/m ³	250	ppm(V)
Maximum limit value; Skin resorption / sensibilisation: Pregnancy group: Status: 2011				

Xylene

List	EH40			
Type	WEL			
Value	220	mg/m ³	50	ppm(V)
Short term exposure limit	441	mg/m ³	100	ppm(V)
Maximum limit value; Skin resorption / sensibilisation: Sk; Pregnancy group; Status: 2005				

Derived No/Minimal Effect Levels (DNEL/DMEL)

Styrene

Reference substance	Styrene			
DNEL				
Conditions	Worker	Acute	inhalative	Systemic effects
Concentration	289	mg/m ³		
DNEL				
Conditions	Worker	Long term	inhalative	Systemic effects
Concentration	85	mg/m ³		
DNEL				
Conditions	Worker	Acute	inhalative	Local effects
Concentration	306	mg/m ³		
DNEL				

* BÜFA®-UP HARZ 65 T (MINKE I)

Date revised: 30.05.2015

7000165

Version: 7 / GB

Master No. M-401

Print date: 16.06.15

Conditions	Worker	Long term	dermal	Systemic effects
Concentration	406	mg/kg/d		

Xylene

DNEL				
Conditions	Worker	Short term	inhalative	Systemic effects
Concentration	289	mg/m ³		

DNEL				
Conditions	Worker	Short term	inhalative	Local effects
Concentration	289	mg/m ³		

DNEL				
Conditions	Worker	Lifetime	dermal	Systemic effects
Concentration	180	mg/kg		

DNEL				
Conditions	Worker	Lifetime	inhalative	Systemic effects
Concentration	77	mg/m ³		

8.2. Exposure controls**Appropriate engineering controls**

Use only in well ventilated areas.

Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

General protective and hygiene measures

Provide good ventilation of working area (local exhaust ventilation if necessary). Avoid contact with skin and eyes. Do not inhale gases/vapours/aerosols.

Respiratory protection

If workplace limits are exceeded, a respiratory protection approved for this particular job must be worn.

Short term: filter apparatus, Filter A

Hand protection

Chemical resistant gloves

Appropriate Material	Butyl rubber		
Material thickness	0,7	mm	
Breakthrough time	= 30	min	

Eye protection

Tightly fitting safety glasses

Body protection

Clothing as usual in the chemical industry.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Form	liquid		
Colour	transparent		
Odour	of styrene		
Flash point			
Value	32		°C
Efflux time			
Value	> 61		s
Method	DIN EN ISO 2431 - 6 mm		
Density			
Value	1,2		g/cm ³

* BÜFA®-UP HARZ 65 T (MINKE I)

Date revised: 30.05.2015

7000165

Version: 7 / GB

Master No. M-401

Print date: 16.06.15

Temperature 20 °C

9.2. Other information

No information available.

SECTION 10: Stability and reactivity**10.1. Reactivity**

No hazardous reactions when stored and handled according to prescribed instructions.

10.2. Chemical stability

The product is stable.

10.3. Possibility of hazardous reactions

Under normal conditions of storage and use, hazardous reactions will not occur.

10.4. Conditions to avoid

Protect from heat and direct sunlight.

10.5. Incompatible materials

Reactions with peroxides and other radical components.

10.6. Hazardous decomposition products

No hazardous decomposition products known.

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute oral toxicity**

ATE	>	10.000	mg/kg
Method		calculated value	

Acute oral toxicity (Components)**Styrene**

Species	rat		
LD50	>	5000	mg/kg

Acute dermal toxicity

ATE	>	10.000	mg/kg
Method		calculated value	

Acute dermal toxicity (Components)**Styrene**

Species	rat		
LD50	>	5000	mg/kg

Acute inhalational toxicity

ATE		32,01	mg/l
Administration/Form		Vapors	
Method		calculated value	

ATE		4,08	mg/l
Administration/Form		Dust/Mist	
Method		calculated value	

Acute inhalative toxicity (Components)**Styrene**

Species	rat		
LC50		11,8	mg/l
Duration of exposure		4	h
Administration/Form		Vapors	

Skin corrosion/irritation

Irritating effects on the skin and mucous membrane.

* BÜFA®-UP HARZ 65 T (MINKE I)

Date revised: 30.05.2015

7000165

Version: 7 / GB

Master No. M-401

Print date: 16.06.15

Serious eye damage/irritation

Eye contact with the product may lead to irritation.

Sensitization (Components)**Styrene**

evaluation non-sensitizing

Mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity (STOT)**Repeated exposure**Reference substance Styrene
Route of exposure inhalative
Organs: Ear**Other information**

Inhalation of the vapours causes irritation of the respiratory tract and mucous membrane, headaches, nausea, giddiners, vomiting.

SECTION 12: Ecological information**12.1. Toxicity****Fish toxicity****Styrene**

LC/EC/IC50 > 1,0 to 10 mg/l

Daphnia toxicity**Styrene**Species Daphnia magna
LC/EC/IC50 > 1,0 to 10 mg/l**Algae toxicity****Styrene**

LC/EC/IC50 > 1,0 to 10 mg/l

Bacteria toxicity

No toxicological data are available.

12.2. Persistence and degradability

For this subsection there is no ecotoxicological data available on the product as such.

Biodegradability**Styrene**

evaluation Readily biodegradable (according to OECD criteria)

12.3. Bioaccumulative potential

For this subsection there is no ecotoxicological data available on the product as such.

12.4. Mobility in soil

For this subsection there is no ecotoxicological data available on the product as such.

12.5. Results of PBT and vPvB assessment

The product does not contain PBT/vPvB-substances.

12.6. Other adverse effects

For this subsection there is no ecotoxicological data available on the product as such.

* BÜFA®-UP HARZ 65 T (MINKE I)

Date revised: 30.05.2015

7000165

Version: 7 / GB

Master No. M-401

Print date: 16.06.15

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations for the product

EWC waste code 07 02 08* other still bottoms and reaction residues
The listed waste code numbers, according to the European Waste Catalogue (EWC), are to be understood as a recommendation. A final decision must be made in agreement with the regional waste disposal company.

Disposal recommendations for packaging

Packaging that cannot be cleaned should be disposed off as product waste.

SECTION 14: Transport information

Land transport ADR/RID

14.1. UN number

UN number 1866

14.2. UN proper shipping name

RESIN SOLUTION

14.3. Transport hazard class(es)

Class 3

14.4. Packing group

Packing group III
Special provision 640E
Remarks Viscous product: Transport according to paragraph 2.2.3.1.5 ADR/RID
Tunnel restriction code D/E

Marine transport IMDG/GGVSee

14.1. UN number

UN number 1866

14.2. UN proper shipping name

RESIN SOLUTION

14.3. Transport hazard class(es)

Class 3

14.4. Packing group

Packing group III
Remarks Transport according to 2.3.2.5 of the IMDG Code
EmS F-E, S-E

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC

VOC (EU) 1,2 %

Other information

The product does not contain substances of very high concern (SVHC).

15.2. Chemical safety assessment

No information available

SECTION 16: Other information

Hazard statements listed in Chapter 3

H226 Flammable liquid and vapour.
H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.

* BÜFA®-UP HARZ 65 T (MINKE I)

Date revised: 30.05.2015

7000165

Version: 7 / GB

Master No. M-401

Print date: 16.06.15

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H361d	Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure:
H373	May cause damage to organs through prolonged or repeated exposure:

Abbreviations

CAS: Chemical Abstracts Service
 EAK: Europäischer Abfallkatalog
 EINECS: European Inventory of Existing Commercial Chemical Substances
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: Very persistent and very bioaccumulative
 VOC: Volatile Organic Compound

CLP categories listed in Chapter 3

Acute Tox. 4	Acute toxicity, Category 4
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Dam. 1	Serious eye damage, Category 1
Eye Irrit. 2	Eye irritation, Category 2
Flam. Liq. 3	Flammable liquid, Category 3
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin irritation, Category 2
Skin Sens. 1	Skin sensitization, Category 1
STOT RE 1	Specific target organ toxicity - repeated exposure, Category 1
STOT RE 2	Specific target organ toxicity - repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity - single exposure, Category 3

Supplemental information

Relevant changes compared with the previous version of the safety data sheet are marked with: ***
 This information is based on our present state of knowledge. However, it should not constitute a guarantee for any specific product properties and shall not establish a legally valid relationship.